

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

Delphion

RESEARCH

INTEGRATED IAM

SERVICES

INSIDE DELPHION

My Account | Products | Events

Search: Quickfinder Boolean Advanced

## The Delphion Integrated View

Buy Now:  PDF | [More choices...](#)Tools: Add to Work File: [Create new Work File](#) View: INPADOC | Jump to: [Top](#)  [Email this to a friend](#)

 Title: **JP2000228193A2: CARBONACEOUS NEGATIVE ELECTRODE ACTIVE MATERIAL FOR NONAQUEOUS SECONDARY BATTERY AND NONAQUEOUS SECONDARY BATTERY**

 Country: JP Japan  
 Kind: A2 Document Laid open to Public inspection


 Inventor: KINOSHITA SHINICHI;  
 OKAHARA KENJI;  
 KATO AKIO;  
 YAMAGUCHI SHOJI;


 Assignee: MITSUBISHI CHEMICALS CORP  
[News, Profiles, Stocks and More about this company](#)


 Published / Filed: Aug. 15, 2000 / Feb. 4, 1999


 Application Number: JP1999000026819


 IPC Code: H01M 4/58; H01M 4/02; H01M 10/40; C01B 31/02;

 Priority Number: Feb. 4, 1999 JP1999000026819

 Abstract: **Problem to be solved:** To provide a negative electrode active material having a high capacity and excellent efficiency, and a nonaqueous secondary battery using it.  
**Solution:** This carbonaceous negative electrode active material is composed of a mixture of at least graphite and fired carbon. The fired carbon has such a pore distribution by a BET adsorption method of gaseous nitrogen that pores having diameters below 8 &angst; exist as many as  $2 \times 10^{-4}$  CC/g or more, and that pores having diameters in the range of 8-18 &angst; exist as many as  $15 \times 10^{-4}$  CC/g or less, and the fired carbon is obtained, for example, by executing a first heat treatment at 250-650°C under an inert gas atmosphere and second heating treatment at 700-1,500°C under an inert gas atmosphere of fine powdery carbonaceous material. This nonaqueous secondary battery has a negative electrode in which this carbonaceous negative electrode active material is used.  
 COPYRIGHT: (C)2000,JPO

 Family: [Show 2 known family members](#)

 Other Abstract Info: CHEMABS 133(12)166262B CHEMABS 133(12)166262B DERABS C2000-596944 DERABS C2000-596944


[View Image](#)

1 page


[this for the Gallery...](#)

[Nominate](#)



(19)

(11) Publication number: **2000228193 A**

Generated Document.

**PATENT ABSTRACTS OF JAPAN**(21) Application number: **11026819**(51) Intl. Cl.: **H01M 4/58 H01M 4/02 H01M 10/40**(22) Application date: **04.02.99**

(30) Priority:

(43) Date of application  
publication: **15.08.00**(84) Designated contracting  
states:(71) Applicant: **mitsubishi chemicals corp**(72) Inventor: **KINOSHITA SHINICHI  
OKAHARA KENJI  
KATO AKIO  
YAMAGUCHI SHOJI**

(74) Representative:

**(54) CARBONACEOUS  
NEGATIVE ELECTRODE  
ACTIVE MATERIAL FOR  
NONAQUEOUS SECONDARY  
BATTERY AND  
NONAQUEOUS SECONDARY  
BATTERY**

(57) Abstract:

**PROBLEM TO BE SOLVED:** To provide a negative electrode active material having a high capacity and excellent efficiency, and a nonaqueous secondary battery using it.

**SOLUTION:** This carbonaceous negative electrode active material is composed of a mixture of at least graphite and fired carbon. The fired carbon has such a pore distribution by a BET adsorption method of gaseous nitrogen that pores having diameters below 8 &angst; exist as many as  $2 \times 10^{-4}$  CC/g or more, and that pores having diameters in the range of 8-18 &angst; exist as many as  $15 \times 10^{-4}$  CC/g or less, and the fired carbon is obtained, for example, by executing a first heat treatment at 250-650°C under an inert gas atmosphere and second

heating treatment at 700-1,500°C under an inert gas atmosphere of fine powdery carbonaceous material. This nonaqueous secondary battery has a negative electrode in which this carbonaceous negative electrode active material is used.

COPYRIGHT: (C)2000,JPO